

#### NFA01250B AirCell® 50 Ohm Connectors

For use with AirCell® 1/2" 50 Ohm Transline and Radiating Cables

Description	NFA01250B
<b>General Specifications</b>	
Interface	N Female
Body Style	Straight
<b>Electrical Specifications</b>	
Impedance, Ohms	50
Operating Frequency Band	0.3 MHz to 3 GHz
Dielectric Withstand Voltage	2 kV DC
3rd Order IMD	-153 dBc minimum, -160 typical
3rd Order IMD, Test Method	2 x 20 Watt carriers
Average Power	0.6 kW
Peak Power, maximum	10 kW
Insertion Loss, typical	0.05
Shielding Effectiveness	-130 dB
Return Loss (VSWR)	
DC to 1 GHz	39 dB (1.02)
1 GHz to 2 GHz	38 dB (1.03)
2 GHz to 3 GHz	34 dB (1.04)
<b>Mechanical Specifications</b>	
Outer Contact Plating	Silver
Inner Contact Plating	Silver
Interface Durability	500 cycles
Interface Durability Test Method	IEC 16916
Minimum Connector Pull-off Force	350 lbs
<b>Environmental Specifications</b>	
Operating Temperature, °F (°C)	-40° to 158° (-40° to 70°)
Storage Temperature, °F (°C)	-40° to 158° (-40° to 70°)
Installation Temperature, °F (°C)	23° to 122° (-5° to 50°)
Immersion Test Method	IEC60529:2001 IP68
Corrosion Test Method	MIL-STD-1344A
Thermal Shock Test Method	MIL-STD-202F
Vibration Test Method	MIL-STD-202F
<b>Regulatory Compliance/Certifications</b>	
RoHS 2011/65/EU Compliant	
TL 9000 H-V	



©2016 Trilogy Communications, Inc. All rights reserved. All trademarks identified by ® are registered trademarks of Trilogy Communications. All Specifications are subject to change without notice. See [www.trilogycoax.com](http://www.trilogycoax.com) or call 800-TRILOGY for the most current information. Revised 09/18/17

**Notice:** Trilogy disclaims any liability or responsibility for the results of improper or unsafe installation, inspection, maintenance or removal practices